

AXIS AX 60

EO GAS STERILIZER



60 liter EO Gas Sterilizer



KORDON

Tıp Sağlık Araç ve Gereçleri

Manufacturer: KORDON TIP SAĞLIK ARAC GEREÇLERİ

PROJ. MUH. İTH.SAN. VE TIC.LTD.STİ.

10006/1 No:43 A.O.S.B CİGLİ İZMİR TÜRKİYE

www.kordontip.com * info@kordontip.com

Tel: +90232.348.60.60 * Fax:+90232.348.60.90

<https://www.youtube.com/channel/UCJfYtHhdi-Zps3ncSUGU9w>



Axis offers the latest technology in gas diffusion sterilization systems. The products to be sterilized are placed in the Liner Bag together with the EO Gas Cartridge, Dosimeter, Humidity Chip and sealed with a tie or a sealing machine. All information on the device is provided to be displayed on the color monitor. All stages such as resistance, fan, vacuum, conditioning, sterilization, ventilation and so on can be easily followed, and visual and auditory warnings are given in case of any malfunction. EO is used in healthcare facilities to sterilize critical items (and sometimes semi-critical items) that are sensitive to moisture or heat and cannot be sterilized by steam or other sterilization methods. Therefore, a wide variety of materials, especially polymeric components commonly used in medical devices, can be sterilized with EO. The cabin is automatically kept under permanent vacuum in all stages (conditioning-sterilization-ventilation) and user safety is ensured.

AX-60 Features	
Capacity	60 liter
Display	Dixell Controller
Internal Dimensions (WxDxL)	35x50x35 cm
External Dimensions (WxDxL)	37x61x41 cm
Weight	23 kg
Power	200W
Voltage	110-220 VAC
Working Temperature	30-59°C
Outer Material	Decorative Inox
Inner Material	Stainless Steel
Safety	Manual Door Lock
Preconditioning	0-9 Hours
Sterilization	1-9 Hours
Aeration	0-9 Hours
Total Cycle Time	1-27 Hours
Liner Bag	47x60 cm
EO Cartridge	ARQ-11 / ARQ-5 / AR-11

- 100% EO and 100% Safe
- Vacuum type sealing and gasket pressure plate
- Sterilization and Ventilation in the same cabinet
- 4 hour short program
- Practical and easy to use
- Robust construction
- Use without failure risk, completely maintenance-free, full work
- MDR compliant, EN 61010-2-40, EN 61010-1, EN 60601-1-2 EMC, EN 60601-1, ISO 9001-13485 with Test and Quality Reports
- New software compatible with EN 14937 for validation studies
- Suitable for invasive sterilization

What can be sterilized with AX 60 EO Gas Sterilizer?

- Heat- sensitive equipment
- Assembled complex devices
- Catheters, stents, syringes, medical gloves,surgical threads
- Custom procedure packs
- Equipment with integrated electronics
- Multi-lumen tubing products
- Wound care dressings
- Plastic, metal, and rubber medical supplies
- Laparoscopic and endoscopic equipment
- Surgical instruments
- Surgical gowns and drapes
- Endoscopes, dental instruments
- Spices; thyme, mint
- Pharmaceutical capsules and boxes,brushes, face powders
- Old books and library applications
- Fabrics, leather, chemical fibers





Axis EO Gas Sterilizers works with;
Axis EO Gas Cartridges (AR series)
 and these are consists of;
 -Liner bag and tie-wrap
 -100% Gas Cartridge of 11g or 5g
 -Humidity Chip
 -Dosimeter Indicator
 -Dosimeter Tracking Form

OR

Axis EO Gas Sterilizers works with;
Axis Ampoule Sets (ARQ series)
 and these are consists of;
 -Liner bag and tie-wrap
 -100% Gas Ampoule of 11g or 5g
 -Humidity Chip
 -Dosimeter Indicator (optional)



The ends of the Axis ethylene oxide ampoules are sealed with hermetic sealing technique.


How does it work?

Simply put items to be sterilized into the Liner bag along with the Gas Ampoule and Humidity Chip than seal the liner bag with any sealing machine or tie-wrap. Then when placing the Liner Bag in the sterilizer, activate the EO gas cartridge and the sterilization process will begin.

Liner bags allows EO gas circulation due its permable stucture. According to EO Gas Sterilizer volume, liner bag dimensions will change.

Humidity chips provide essential moisture inside the bag.





Dixell controller allows user to set up temperature, time, stop and start the cycle.

- A. On/Off Switch / EMERGENCY STOP
- B. Temperature Indicator
- C. Timer
- D. Start / Stop Button
- E. Mechanical Door Lock
- F. Gaskets
- G. Fan

AXIS Sterilizers do not require any pressurized air, water, or drainage. All that is required is a 220V earthed electricity supply and an opening in a wall/window through which the outlet pipe of 6 cm diameter can be connected to the atmosphere.

Axis AX-1800 EO Gas Alarm



- Instant tracking on the screen.
- EO concentration measurement in the range of 0-99 ppm.
- Microprocessor controlled.
- Visual and auditory alarm (> 85 dB).
- Adjustable alarm level.
- Automatic calibration.
- External alarm output.
- Can be mounted on the wall.
- High reliability.
- 220V 50Hz.
- 2-year warranty including sensor.
- Sensor life of up to five years

Kordon Tip Recommends

The advantages of EO Sterilization;

- The widest range of material and product compatibility
- Ability to sterilize long, narrow, and multi-channel lumens.
- All sides and surfaces will be sterilized
- Compatible with all common packaging materials.
- Does not damage delicate instruments like harsh chemical sterilants.

YouTube : Axis EO Sterilizers

